

Design features:

- Constructed using high grade, engineered aluminum
- Tempered clear safety glass
- Available in Chrome, Brushed Nickel or Oil-Rubbed Bronze finishes
- Doors include rollers with long life bearings for years of smooth, maintenance-free operation
- Adjustable for out-of-plumb walls
- Integral pull handle
- Easy to install and clean
- Frameless or framed designs available
- Frameless glass is 3/16" thick

Code Accepted

STYLEMATE® Enclosures meet or exceed performance requirements as listed:

- American National Standards Institute (ANSI) Specification Z 97.1




Specifications


| Model | Finish | Glass | H | Opening | UPC | Fits DURABASE® |
|-------------------------|-------------------|-------|-----|---------|-----------------|--------------------------|
| Framed Design | | | | | | |
| 48.403 | Chrome | Clear | 69" | 47" | 6 71031 00466 6 | 3448M, 3248M |
| 48.404 | Brushed Nickel | Clear | 69" | 47" | 6 71031 00467 3 | 3448M, 3248M |
| 48.405 | Oil-Rubbed Bronze | Clear | 69" | 47" | 6 71031 00468 0 | 3448M, 3248M |
| Frameless Design | | | | | | |
| 48.406 | Chrome | Clear | 69" | 47" | 6 71031 00469 7 | 3448M, 3248M |
| 48.407 | Brushed Nickel | Clear | 69" | 47" | 6 71031 00470 3 | 3448M, 3248M |
| 48.408 | Oil-Rubbed Bronze | Clear | 69" | 47" | 6 71031 00471 0 | 3448M, 3248M |
| Framed Design | | | | | | |
| 60.403 | Chrome | Clear | 69" | 59" | 6 71031 00472 7 | 3260M, 3460M, 3060 (L/R) |
| 60.404 | Brushed Nickel | Clear | 69" | 59" | 6 71031 00473 4 | 3260M, 3460M, 3060 (L/R) |
| 60.405 | Oil-Rubbed Bronze | Clear | 69" | 59" | 6 71031 00474 1 | 3260M, 3460M, 3060 (L/R) |
| Frameless Design | | | | | | |
| 60.406 | Chrome | Clear | 69" | 59" | 6 71031 00475 8 | 3260M, 3460M, 3060 (L/R) |
| 60.407 | Brushed Nickel | Clear | 69" | 59" | 6 71031 00476 5 | 3260M, 3460M, 3060 (L/R) |
| 60.408 | Oil-Rubbed Bronze | Clear | 69" | 59" | 6 71031 00477 2 | 3260M, 3460M, 3060 (L/R) |

Framed Design:

Frameless Design:



General: Furnish and install as shown on plans, a STYLEMATE® By-Pass enclosure as manufactured by E.L. Mustee & Sons, Inc. Model _____ with a bright (Chrome, Brushed Nickel, Oil-Rubbed Bronze) finish. Shall be by-pass style with aluminum frame and clear tempered safety glass panel. Continuous pull handle. Out-of-plumb condition up to 1" can be adjusted. Shall meet ANSI Specifications Z97.1



General: Furnish and install as shown on plans, a STYLEMATE® Frameless By-Pass enclosure as manufactured by E.L. Mustee & Sons, Inc. Model _____ with a bright (Chrome, Brushed Nickel, Oil-Rubbed Bronze) finish. Shall be a frameless style by-pass door with aluminum top and bottom track and clear tempered safety glass panels. Continuous pull handle. Out-of-plumb condition up to 1" can be adjusted. Shall meet ANSI Specifications Z97.1

